


Bülte | Slotted plug BPE 157 in PE-HD





Details du produit

Description

For the protection of threaded bores from dirt and external contaminates. Can also be used to close off a lubrication point.

Advantages

Re-usable and easy to use. Suitable for hand tightening or with a cross head screw driver (Philips)

Qualities

This plug is manufactured in polyethylene which offers good resistance to a range of liquids, dilute acids, and chemicals

usage

They can be used in all sectors of activity. Above all, they provide optimum protection during production, storage and transport. Illustrations are not contractual

| d | dì | D | h | н | L | М | Pitch | Minimum sales Quantity | SKU |
|-----|------|------|-----|-----|------|----|-------|------------------------|-------------|
| M10 | 12,0 | 15,9 | 4,0 | 5,0 | 10,0 | 10 | 1,0 | 5000 | BPE157101 |
| M10 | 12,0 | 15,9 | 4,0 | 5,0 | 10,0 | 10 | 1,5 | 5000 | BPE1571015 |
| M12 | 12,0 | 15,9 | 4,0 | 5,0 | 10,0 | 12 | 1,0 | 5000 | BPE157121 |
| M12 | 12,0 | 15,9 | 4,0 | 5,0 | 10,0 | 12 | 1,5 | 5000 | BPE1571215 |
| M12 | 12,0 | 15,9 | 4,0 | 5,0 | 10,0 | 12 | 1,8 | 5000 | BPE15712175 |
| M4 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 4 | 0,7 | 5000 | BPE157407 |
| M5 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 5 | 0,8 | 5000 | BPE157508 |

| d | dl | D | h | Н | L | М | Pitch | Minimum sales Quantity | SKU |
|----|------|------|-----|-----|-----|---|-------|------------------------|------------|
| М6 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 6 | 0,8 | 5000 | BPE1576075 |
| М6 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 6 | 1,0 | 5000 | BPE15761 |
| М8 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 8 | 1,0 | 5000 | BPE15781 |
| M8 | 12,0 | 15,9 | 4,0 | 5,0 | 8,0 | 8 | 1,3 | 5000 | BPE1578125 |





Bülte England

37B Basepoint Centre Harts Farm Way Havant Hampshire PO9 1HS